Calibrating the RT300 Ergometer

Leg ergometer calibration

- 1. Power on the RT300 and wait for the main "GO" page to appear
- 3. Tap Menu and then Login
- 5. Tap Start Calibration



- 2. Remove the pedals from the RT300
- 4. Enter the calibration code 4102410039 and then tap OK in the bottom right
- 6. Lock the pedals in place by attaching the wheelchair restraint to the crank



- 7. Tap "Crank is locked" and the first phase of the calibration process will commence
 - ID: None
 Rx
 If < 5:18</td>
 0k

 I hours since last calibration.
 I hours since last calibration.
 I hours since last calibration.

 1 hours use total.
 Calibrated:

 Please lock the ergometer leg crank.

 Image: Crank is locked.

8. Tap "Click to continue"

10. Tap "Crank is unlocked"

🐈 ID: None Rя 🛛 📰 📢 5:25 ok
Leg v JxR 103 v MR v Write 1 hours since last calibration. 1 hours use total. Last Calibrated:
IxR Calibration finished.
Click to continue

9. Remove the wheelchair restraint from the pedal crank so that it can rotate freely

- ID: None
 Rx
 If < 5:26</td>
 ok

 Image: State of the state
- 11. Wait for the 2nd phase of calibration process
- 12. Tap "Click to close dialog"

to complete

🏄 ID: None Rx 🛛 💥 ┥€ 5:27 ok	/ <mark>}</mark> / ID: None Rx 🛛 🗱 ◄< 5:27 🔤 k	
Leg v DxR 103 v MR v Write 1 hours since last calibration. 1 hours use total. Last Calibrated:	Leg v DrR 103 v MR 5 v Write O hours since last calibration. 1 hours use total. Last Calibrated: 11/27/07 5:27:38 AM	
MR Calibration in progress.	Mechanical resistance calibration finished. Calibration successfully completed.	
Cancel	Elick to close dialog.	

13. Refit the pedals. Be sure to tighten the retaining bolt well

Arm ergometer calibration

- 1. Power on the RT300 and wait for the main "GO" page to appear
- 3. Tap Menu and then Login
- 5. Select Arm and then tap Start Calibration
- ID: None
 Rx
 Image: Control of the start calibration
 Image: Control of the start calibration

 Start Calibration
 Start Calibration
 Image: Control of the start calibration
 Image: Control of the start calibration

 Start Calibration
 Start Calibration
 Image: Control of the start calibration

- 2. Remove the pedals from the RT300
- 4. Enter the calibration code 4102410039 and then tap OK in the bottom right
- Lock the arm crank in place by turning the arm crank lock knob until it "clicks into place"



- 7. Tap "Crank is locked" and the first phase of the calibration process will commence
- 8. Tap "Click to continue"



 Release the arm crank lock knob by pulling it down and turning it ½ turn in either direction
 Tap "Crank is unlocked"





- 11. Wait for the 2nd phase of calibration process to complete
- 12. Tap "Click to close dialog"

19 I I	ID: None Rx	1	ID: None Rx 🛛 🗱 ╡€ 5:27 🛛 ok	
1 hc	I VR 103 Y MR Y Write ours since last calibration. ours use total.		Leg v JuR 103 v MR 5 v Write D hours since last calibration. 1 hours use total. ast calibrated: 11/27/07 5:27:38 AM	
MR.	Calibration in progress.		Mechanical resistance calibration finished. Calibration successfully completed.	
	Cancel		Click to close dialog.	